

## SUPPLEMENTAL/BID BULLETIN NO. 7

### SUPPLY AND DELIVERY OF ICT EQUIPMENT (DOT-BAC-IB NO. 2020-004)

This **Supplemental/Bid Bulletin No. 7** is issued to all prospective bidders to further modify and/or amend items in the Bidding Documents for the aforementioned project. This shall form part of the Bidding Documents.

#### I. AMENDMENT TO BIDDING DOCUMENTS

#### A. Section VII. Technical Specifications

ltem	Specifications
Item Lot No. 3	Specifications         MOBILE DEVICES:         1. Mobile Tablet – 40 units         2. Printer (All in One) – 34 units         3. Compact/Portable Scanner – 34 units         4. DSLR Camera – 15 units         Technical Specifications:         3. Compact/Portable Scanner
	Memory: At least <u>64MB</u>

Please use the attached Revised Technical Specifications together with all other required documents for the Bid Opening on June 10, 2020, 2:30 PM.

For the guidance and information of all concerned.

03 June 2020

IN . ROBERTO P. ALABADO III DOT-BAC Chairperson

# Section VII. Technical Specifications

ltem	Specification	Statement of Compliance <sup>1</sup>
Lot No. 1	DESKTOP (190 units) This Desktop specification is configured to order and intended for enterprise/business not for consumer use. It is created for the unique needs of small business with advanced processors and an array of options in an ultra-compact design.	
	I. IT Supplier Requirement for Desktop:	
	<ol> <li>Must submit certification of authorized partner.</li> <li>Must provide a central toll-free hotline number and e-mail address of the brand being offered.</li> <li>On - site support shall be provided by the manufacturer on the Next Business Day after final remote diagnosis for delivered items within Metro Manila and 3 days outside Metro Manila</li> <li>On - site support engineers and technicians should carry a valid manufacturer's ID and certification from the brand or manufacturer of the delivered ICT equipment especially on desktop, laptop and servers.</li> <li>Unit model must be current and not in "end of Life" as reflected in the current product line found in the manufacturer's official website / brochure. A manufacturer's certificate for this purpose is required.</li> <li>Certification from the brand and product manufacturer that the brand and product parts being offer will be available and serviceable for at least five (5) years after delivery and acceptance.</li> <li>All components must conform to international standards and should be factory installed with corresponding part number and verifiable via web.</li> <li>The manufacturer brand must have at least two parts depot within the country to ensure sufficient number of spare parts</li> </ol>	

<sup>&</sup>lt;sup>1</sup> Bidders must state here either "Comply" or "Not Comply" against each of the individual parameters of each Specification stating the corresponding performance parameter of the equipment offered. Statements of "Comply" or "Not Comply" must be supported by evidence in a Bidders Bid and cross-referenced to that evidence. Evidence shall be in the form of manufacturer's un-amended sales literature, unconditional statements of specification and compliance issued by the manufacturer, samples, independent test data etc., as appropriate. A statement that is not supported by evidence or is subsequently found to be contradicted by the evidence presented will render the Bid under evaluation liable for rejection. A statement either in the Bidders statement of compliance or the supporting evidence that is found to be false either during Bid evaluation, post-qualification or the execution of the Contract may be regarded as fraudulent and render the Bidder or supplier liable for prosecution subject to the provisions of **ITB** Clause **Error! Reference source not found.** and/or **GCC** Clause **Error! Reference source not found.** 

	Technical Specifications:
En	terprise / business model Desktop
No	t less than 19.5" Monitor including the bezel <u>or</u> 18.5" active display
Eq	uivalent to 9th Generation Intel Core i5 – 9400 Processor (6 Core, 9MB Cache, up to 4.1Ghz) Intel Turbo Boost or higher
	A (Environment Protection Agent) Chassis MOD DW PSU with Trust Platform Module (TPM)
	*as compliance to Climate Change and DOT sustainable tourism
	*as compliance to data privacy act
Tra	ay Load DVD Drive (Read and Write) <b>must include</b> Bezel with Slim Optical Drive (Reads and Writes)
Eq	uivalent to Wireless 1707 Card (802.11bgn + Bluetooth 4.0, 2.4GHz)
10	Bigabit Lan port
Ex	factory Delivery
8G	B DDR4, 2666MHz UDIMM Non-ECC; up to 32GB
Inte	egrated Graphics
1TI	B 7200RPM SATA 6Gb/s HDD
En	ergy Star Label
Wi	red Mouse Same brand of desktop Black
Wi	red Keyboard Same brand of desktop Black
Lat	test Propriety Operating System (Professional) 64 bit
Мо	d Spec Info
RE	G label for Eagle Small Form Factor-Environment Protection Agent (SFF-EPA)
Fix	ed Hardware Configuration
*Tł	his help the IT Division to identify and verify that the products was ship directly from the manufacturer and no alteration while delivery is in progress.
Wa	arranty:
Lin	nited Warranty: 3 years labor and parts – PH
3Y	r Technical Support –PH
Ра	rts and labor response
7x2	24 Technical Support & Assistance:PH
Sa	me or NBD Onsite Service – PH

	Direct Online cases and dispatch
	Dispatch monitoring and crisis management
	Escalation management
	Collaborative 3rd party assistance
	Predictive / proactive automated issue detection, notification and case creation
	Predictive / proactive issue detection for failure prevention
	VIP / Priority Access to engineers
	Accidental damage repair
	Hard Drive Retention
	Dedicated Technical Account Handler
	Monthly support history and contract reporting
Lot No. 2	LAPTOP (130 units)
	This Laptop specification is configured to order and intended for enterprise/business not for consumer use.
	I. IT Supplier Requirement for Laptop
	1. Must submit certification of authorized partner.
	<ol> <li>Must provide a central toll-free hotline number and e-mail address of the brand being offered.</li> </ol>
	<ol> <li>On - site support shall be provided by the manufacturer on the Next Business Day after final remote diagnosis for delivered items within Metro Manila and 3 days outside Metro Manila</li> </ol>
	4. On - site support engineers and technicians should carry a valid manufacturer's ID and certification from the brand or manufacturer of the delivered ICT equipment especially on desktop, laptop and servers.
	5. Unit model must be current and not in "end of Life" as reflected in the current product line found in the manufacturer's official website / brochure. A manufacturer's certificate for this purpose is required.
	<ol> <li>Certification from the brand and product manufacturer that the brand and product parts being offer will be available and serviceable for at least five (5) years after delivery and acceptance.</li> </ol>
	<ol> <li>All components must conform to international standards and should be factory installed with corresponding part number and verifiable via web.</li> </ol>

 8. The manufacturer brand must have at least two parts depot within the country to ensure sufficient	
number of spare parts.	
II. Technical Specifications:	
Enterprise or Business model Laptop	
Equivalent to 10th Generation Intel Core i5 – 10210U Processor (6Mb Cache, up to 4.2Ghz) or higher	
14.0" FHD (1920 x 1080) Anti- Glare LED – Backlit Non-touch WVA Display	
LCD Cover Kit – Black Palmrest with Finger Print Reader	
*The finger print reader can be located anywhere in the palmrest even beside or on the power button	
Trust Platform Module (TPM) on board	
8GB DDR4 2666MHz	
1TB 5400 rpm 2.5" SATA Hard Drive	
Energy Star Label	
Equivalent to Intel(R) UHD Graphics	
802.11ac 1x1 Wireless and Bluetooth	
English International non – backlit keyboard	
Latest Propriety Operating System (Professional) 64 bit	
OS Recovery - USB	
Ex-factory Delivery	
FGA NB1 – OU – BTO ex-hub	
Ports:	
2x USB 3.1 Gen 1 port	
1x USB 2.0 port	
1x HDMI	
1x SD 3.0 memory card reader	
1x RJ-45	
1× security lock	
Less than 2kg	

	Warranty and Support:
	Limited Warranty: 3 years labor and parts – PH
	: at least 1 year on battery and
	accessories
	3Yr Technical Support –PH
	Parts and labor response
	7x24 Technical Support & Assistance: PH
	Same or NBD Onsite Service – PH
	Direct Online cases and dispatch
	Dispatch monitoring and crisis management
	Escalation management
	Collaborative 3rd party assistance
	Predictive / proactive automated issue detection, notification and case creation
	Predictive / proactive issue detection for failure prevention
	VIP / Priority Access to engineers
	Accidental damage repair
	Hard Drive Retention
	Dedicated Technical Account Handler
	Monthly support history and contract reporting
	Accessories
	Laptop Backpack must fit most laptops up to 15"
	Wireless Travel Mouse Same brand of laptop – Black
Lot No. 3	MOBILE DEVICES
LOUNO. 5	1. Mobile Tablet - 40 units
	2. Printer (All in One) – 34 units
	3. Compact/Portable Scanner – 34 units
	<i>4. DSLR Camera – 15 units</i>

 Technical Specifications:
1. Mobile Tablet (model must be 2018 or above)
Storage Capacity: 64GB or higher
Size: not more than 204mm x 135 mm x 7mm
Weight: not more than 309g
Display:
7– 8 inch (diagonal) LED-backlit Multi-Touch display
2048 – by – 1536 resolution
Wide color display
True Tone Display
Fingerprint – resistant oleophobic coating
Fully laminated display
Antireflective coating
At least 1.8% reflectivity
At least 500 nits brightness
Chip: must have a 64bit architecture
Rear Camera:
At least 8 mp camera
Five – element lens
Hybrid IR filter
Backside Illumination
Wide color capture for photos and live photos
Autofocus
Panorama
HDR for photos
Exposure control
Burst mode
Tap to focus
Timer mode
Auto image stabilization
Photo geotagging
Video Recording:
1080p HD video recording
Slo – mo (120fps)

Time - lapse video with stabilization /ideo image Stabilization 8x video zoom /ideo geotagging Front Camera: At least 7mp 080p HD video recording at 30 fps Retina Flash Vide color capture for photos and Live Photos Auto HDR for photos and videos Backside illumination Burst mode Exposure control Timer mode Call Function: Audio and Video Call enable
At least 7mp 0800 HD video recording at 30 fps Retina Flash Vide color capture for photos and Live Photos Auto HDR for photos and videos Backside illumination Burst mode Exposure control Timer mode
/ideo geotagging Front Camera: At least 7mp 1080p HD video recording at 30 fps Retina Flash Wide color capture for photos and Live Photos Auto HDR for photos and videos Backside illumination Burst mode Exposure control
Front Camera: At least 7mp 1080p HD video recording at 30 fps Retina Flash Wide color capture for photos and Live Photos Auto HDR for photos and videos Backside illumination Burst mode Exposure control
At least 7mp 1080p HD video recording at 30 fps Retina Flash Wide color capture for photos and Live Photos Auto HDR for photos and videos Backside illumination Burst mode Exposure control
080p HD video recording at 30 fps Retina Flash Wide color capture for photos and Live Photos Auto HDR for photos and videos Backside illumination Burst mode Exposure control
Retina Flash Wide color capture for photos and Live Photos Auto HDR for photos and videos Backside illumination Burst mode Exposure control
Vide color capture for photos and Live Photos Auto HDR for photos and videos Backside illumination Burst mode Exposure control
Auto HDR for photos and videos Backside illumination Burst mode Exposure control
Backside illumination Burst mode Exposure control
Burst mode Exposure control Fimer mode
Exposure control
Timer mode
Call Function: Audio and Video Call enable
Speakers: Stereo Speakers
<b>/licrophones</b> : Dual microphones for calls, video ecording, and audio recording
Cellular and Wireless bandwidth:
Vi-Fi (802.11a/b/g/n/ac); simultaneous dual band 2.4GHz and 5GHz); HT80 with MIMO
Bluetooth 5.0 technology
JMTS/HSPA/HSPA+/DC-HSDPA (850, 900, 700/2100, 1900, 2100 MHz); GSM/EDGE (850, 900, 800, 1900 MHz)
Gigabit-class LTE (Bands 1, 2, 3, 4, 5, 7, 8, 11, 12, 3, 14, 17, 18, 19, 20, 21, 25, 26, 28, 29, 30, 34, 38, 39, 40, 41, 46, 66)
Sim card: Equivalent to Nano – Sim
location:
Digital compass Vi-Fi nicrolocation Assisted/Built-in GPS, GNSS/GLONASS Cellular
Sensors:
Three-axis gyro Accelerometer Barometer Ambient light sensor

Battery:	
Built-in 19.1-watt-hour rechargeable lithium-polymer battery	
Up to 10 hours of surfing the web on Wi Fi, watching video, or listening to music	
Charging via power adapter or USB to computer system	
Up to 9 hours of surfing the web using cellular data network	
Accessibility:	
VoiceOver	
Zoom	
Magnifier	
Dictation	
Switch Control	
Closed Captions	
AssistiveTouch	
Speak Screen	
Audio Playback:	
Audio formats supported: AAC (8 to 320 Kbps), Protected AAC, HE-AAC, MP3 (8 to 320 Kbps), MP3 VBR, Dolby Digital (AC-3), Dolby Digital Plus (E-AC- 3), Audible (formats 2, 3, 4, Audible Enhanced Audio, AAX, and AAX+), AIFF, and WAV	
User-configurable maximum volume limit	
Video Playback:	
H.264 video up to 4K, 30 frames per second, High Profile level 4.2 with AAC LC audio up to 160 Kbps, 48kHz, stereo audio or Dolby Audio up to 1008 Kbps, 48kHz, stereo or multichannel audio, in .m4v, .mp4, and .mov file formats; MPEG 4 video up to 2.5 Mbps, 640 by 480 pixels, 30 frames per second, Simple Profile with AAC LC audio up to 160 Kbps per channel, 48kHz, stereo audio or Dolby Audio up to 1008 Kbps, 48kHz, stereo or multichannel audio, in .m4v, .mp4, and .mov file formats; Motion JPEG (M JPEG) up to 35 Mbps, 1280 by 720 pixels, 30 frames per second, audio in ulaw, PCM stereo audio in .avi file format	
Mail attachment Support:	
.jpg, .tiff, .gif (images); .doc and .docx (Microsoft Word); .htm and .html (web pages); .key (Keynote); .numbers (Numbers); .pages (Pages); .pdf (Preview and Adobe Acrobat); .ppt and .pptx (Microsoft PowerPoint); .txt (text); .rtf (rich text format); .vcf	

(contact informati .zip; .ics	on); .xls and .xlsx (Microsoft Excel);	
Environmental R	Requirements:	
Operating ambier	nt temperature:0° to 35° C	
Non operating ter	nperature:–20° to 45° C	
Relative humidity	: 5% to 95% noncondensing	
Operating altitude	e: tested up to 3,000 meters	
Accessories		
Must have at leas mobile device	t sleeve <u>or smart cover</u> for the	
Warranty and Su	ıpport	
	ranty and 90 days complimentary al support with regional service	
Protection Plan		
An additional/exte	ended 1-year warranty.	
Direct access to e	experts	
Carry – in repair		
Hardware covera	ge	
Unit		
Battery		
Port		
Usb and power a	dapter	
2. Printer (All in One)		
Function:	Print, copy, scan	
Print Speed:	At least 32 ppm (letter,Draft) At least 22 ppm (letter, ISO black) At least 18 ppm (letter, ISO color)	
Print Resolution:	Black(best): At least 1200 x 1200 dpi	
	Color(best): At least 4800 x 1200 dpi	
Print Technology:	Thermal Inkjet	
Borderless Printin	g: Yes (up to letter and A4)	
Energy Star:	Yes	
Scan Type:	Easy slide-off glass	
	2-sided Automatic Document Feeder	

	Contact Image Sensor
Scan Resolutio	n: Max 1200 x 1200 dpi (both hardware and optical)
Scan File Form	at: JPG, BMP, TIFF, PDF, RTF, TXT, PNG
Scan Size (Max	.): ADF: 8.5 x 14 inches
	Flatbed: 8.5 x 11.7 inches
Scanner Featur	es: Optical Character Recognition
	1-click customizable scan to cloud destination
	Create editable
	Searchable document
	Dropbox
	Google Drive
	One Drive
Copy speed:	At least Black (ISO): 21 cpm
	At least Color (ISO): 15 cpm
Copy Resolutio	n: Maximum 600 x 600 dpi (black and color, text and graphics)
<b>Copy Resize</b> : 25 – 400%	
Copier Settings	: Copies; Two-Sided; Lighter/Darker; Copy Fix; ID Copy; Resize; Quality; Paper Size;
	Paper Type; Collate; Margin Shift; Crop;Copy Preview; Enhancements
Connectivity:	1 USB 2.0; 1 Host USB (print from JPEG,TIFF,DPOF 1.1, Exif 2.3, PNG); 1 Ethernet; 1
	Wireless 802.11b/g/n; 2 RJ-11 modem ports
	Yes, via built-in Ethernet, wireless 802.11b/g/n
	At least compatible with Apple AirPrint™; Mobile Apps; Wi-Fi® Direct Printing; Mopria™ Certified; Smart
Memory : At leas	st 512MB
Processor Spee	ed: At least 1.2 Ghz
Control Panel:	At least 6.75 cm touchscreen with color graphic display
	At least 3 buttons

Duty Cycle: 25,000 pages per month	
<b>Media Types</b> : Plain Paper, Photo Papers, Matte Brochure or Professional Paper, Matte	
Presentation Paper, Glossy Brochure or Professional Paper, Other Photo Inkjet	
Papers, Other Matte Inkjet Papers, Other Glossy Inkjet Papers, Thick Plain Paper,	
Light/Recycled Plain Paper, Tri-fold Brochure Paper, Glossy	
<b>Media Sizes</b> : Letter; Legal; Government Legal; Executive; Statement; 3 x 5 in; 4 x 6 in; 5 x 7 in; 13 x	
18 cm; 8 x 10 in; 10 x 15 cm; L; Photo 2L; Envelope( #10, Monarch, 5.5 bar); Card (3 x 5	
in, 4 x 6 in, 5 x 8 in)	
<b>Paper Handling</b> : 250-sheet input tray; Up to 100 sheets with Smart output management; Duplex	
Options: Automatic (standard); Auto Document Feeder Capacity: Standard, 35 sheets;	
Envelope Feeder: No; Standard Paper Trays: 1; Input Capacities: Up to 250 sheets	
standard; Up to 30 envelopes; Up to 50 sheets; Up to 50 sheets labels; Up to 250	
sheets legal; Output Capacities: Up to 60 sheets standard; Up to 10 envelopes; Up to	
30 cards; Up to 30 sheets labels; Up to 60 sheets legal	
<b>Dimension W x D x H:</b> Must not exceed 18 x 21 x 12 inches	
Compatible Operating Systems:	
Windows 10, 8.1, 8, 7,Windows Server 2008 R2 64- bit, Windows Server 2008 R2	
64-bit (SP1), Windows Server 2012 64-bit, Windows Server 2012 R2 64-bit, Windows	
Server 2016	
Compatible Network Operating Systems:	
Windows 10, 8.1, 8, 7: 32-bit or 64-bit	
Power: Internal Universal Power Supply	
100 – 240 VAC (+/- 10%) 50/60 Hz	

3. Compact/Portable Scanner	
Scan Technology: CMOS CIS	
Scan Speed ADF: At least 30 ppm (letter)	
<b>File Format</b> : For text & images: PDF, JPEG, PNG, BMP, TIFF, Text (.txt), Rich Text (rtf) and Searchable PDF	
Energy Star: Yes	
Scan Resolution: At least 600 dpi (hardware and optical; color and mono)	
<b>Media Size</b> : U.SLetter: 215.9 x 279.4 mm (8.5 x 11 in); U.SLegal: 215.9 x 355.6 mm (8.5 x 14 in); U.SExecutive: 184.2 x 266.7 mm (7.25 x	
10.5 in); ISO A4: 210 x 297 mm (8.3 x 11.7 in); JIS B5: 182 x 257 mm (7.2 x 10.1 in); ISO B5: 176 x 250 mm (7.0 x 9.9 in); ISO A5:	
148 x 210 mm (5.8 x 8.3 in); ISO A6: 105 x 148 mm (5.8 x 4.1 in); ISO A7: 74 x 104 mm (2.9 x 4.1 in); ISO A8: 52 x 74 mm (2.0 x	
2.9 in)	
Media Weight: Able to handle at least 50 – 180 g/m2	
DimensionMust not exceed 300 x 173 x 154mm (W x D xH)	
Duty Cycle: At least 2000 pages per day	
ADF Capacity: At least 50 sheets	
Connectivity: USB 2.0	
Memory: At least 64 MB	
<b>Control Panel</b> : Scan button, Power button with a LED and a LED for Error indication	
Compatible Operating Systems:	
OS X Mavericks 10.9, OS X Yosemite 10.10, OS X El Capitan 10.11, Microsoft® Windows® 10, 8.1, 8, 7: 32-bit or 64-bit	
Warranty: 1 Year Limited Warranty	
<b>Electromagnetic emission standard</b> : Class B Emissions; CISPR 22:2008 (International); European Union EMC Directive 2014/30/EU, EN 55022:2010 (CE mark); EN 61000-3-2:2014 (harmonics); EN 61000-3-3:2013 (flicker); Immunity CISPR 24:2010, EN 50024:2010	
Safety Approvals and Requirements: IEC 60950- 1:2005 +A1+A11+A12 and all applicable amendments; CSA/UL 60950-1, 2nd edition (2007); EN 60950-1:2006 +A11	
+A1 +A12+A2; EAC safety	

1		
	4. DSLR Camera	
	Image Sensor: APS-C CMOS Sensor	
	Effective Pixels: At least 24 MP	
	<b>Image Processor:</b> Must be enable to enhance and speed up operations while shooting stills or moving images; provide high light sensitivity for high resolution with minimal noise or dirt in dark conditions; capture actions shots with quick continuous shooting.	
	AF Points: At least 45 all cross type	
	<b>AF method:</b> Face+Tracking, Smooth zone, Live 1- point AF Manual focus (approx. 5x / 10x magnification possible)	
	Effective ISO: Min. 100 – Max. 25600	
	Aspect Ratio: 3:2, 4:3, 16:9, 1:1	
	Built – in Flash: Retractable and auto pop-up	
	Anti-flicker: Yes	
	Shutter Speed: must 1/4000 to 30 sec	
	<b>Continuous Shooting Speed:</b> Max. approximately 6.0 shots /sec	
	<b>Exposure Compensation:</b> Manual: ±5* stops in 1/3- or 1/2-stop increments	
	AEB: ±2 stops in 1/3- or 1/2-stop increments	
	AF in Live View: At least Dual Pixel CMOS AF system	
	<b>Creative filter:</b> Grainy B/W, Soft focus, Fish-eye effect, Art bold effect,	
	Water painting effect, Toy camera effect, Miniature effect	
	Movie recording format: Mp4	
	HDR Movie: Yes	
	Movie recording size and frame rate: Full HD (1920x1080) : 59.94p / 50.00p / 29.97p / 25.00p/23.98p	
	HD (1280x720) : 59.94p / 50.00p / 29.97p / 25.00p	
	VGA (620x480) : 29.97p / 25.00p	
	Digital Zoom: Up to 10x	
	Built-in mic: Yes at least stereo	
	<b>LCD Monitor:</b> At least or equivalent Vari-angle 3.0 inch, 1.04 mil dots TFT, Touch Panel	
	Connection: Wifi, Bluetooth, and NFC	
1	Image Resolution: At least capable of the following:	

L (Large) : 24.0 megapixels (6000 x 4000)
M (Medium) : Approx. 10.6 megapixels (3984 x 2656)
S1 (Small 1) : Approx. 5.9 megapixels (2976 x 1984)
S2 (Small 2) : Approx. 3.8 megapixels (2400 x 1600)
RAW : 24.0 megapixels (6000 x 4000)
<b>Image Style:</b> Auto, Standard, Portrait, Landscape, Fine Detail, Neutral, Faithful, Monochrome, User Defined 1 - 3
Manual Focus: Yes
Memory Card Type: SD / SDHC* / SDXC* memory cards *Compatible with UHS-I cards
<b>Metering Mode:</b> 7560-pixel RGB plus IR metering, Evaluative, Partial, Spot, Centre-weighted average
Peripherals Connections: Hi-Speed USB equivalent, GPS Receiver GP-E2, Connect Station CS100 connection;
HDMI mini OUT terminal Type C (Auto switching of resolution) CEC-compatible;
3.5 mm diameter stereo mini-jack Directional Stereo Microphone DM-E1 connection;
For Remote Switch RS-60E3;
Compatible with Wireless Remote Control BR-E1
(Bluetooth connection) and Remote Controller RC-6;
Sensor Size: APS-C
Shooting Mods: Scene Intelligent Auto, Flash Off, Creative Auto, Portrait,Landscape, Close-up, Sports, Special scene modes (Group Photo, Kids, Food, Candlelight, Night Portrait, Handheld Night Scene, HDR Backlight Control), Creative filters (Grainy B/W, Soft focus, Fish-eye effect, Water painting effect, Toy camera effect, Miniature effect, HDR art standard, HDR art vivid, HDR art bold, HDR art embossed)
Program AE, Shutter-priority AE, Aperture-priority AE, Manual exposure
Lens Kit: At least 18mm – 135mm
same brand as the body
Battery Pack: LP-E17
<b>Number of shots:</b> With viewfinder shooting: Approx. 600 shots at room temperature (23°C/73°F), approx. 550 shots at low temperatures (0°C/32°F)
With Live View shooting: Approx. 270 shots at room temperature (23°C/73°F), approx. 230 shots at low temperatures (0°C/32°F)

\*With a fully-charged Battery Pack LP-E17. **Still Image Format:** JPEG, RAW, RAW + JPEG **Viewfinder Coverage:** 95% **Viewfinder type:** Eye-level pentamirror **Weight (with kit lenses):** 1035 **White Balance:** Auto, Preset (Daylight, Shade, Cloudy, Tungsten light, White fluorescent light, Flash), Custom White Balance correction and White balance bracketing possible \*Flash color temperature information transmission enabled **X-sync (sec):** 1/200 **Accessories:** Must include carry in bag

Conforme:

Name of Bidder's Representative

Signature